











Standard Position Hinges & Torque Inserts

MH12		MH-14	
	• Weighs only 15 grams • 270° rotation • 4 torque values • Range 0.4 to 1.6 N-m • Black nylon housing • 25,000 cycle life Additional Product Info		• 270° rotation • 12 torque values • Range 1.4 to 5.8 N-m • Black nylon housing • 20,000 cycle life Additional Product Info
MH15		MH-18	
	• 270° rotation • 7 torque values • Range 2.0 to 8.0 N-m • Asymmetric torque for easy lift • Black nylon housing • 20,000 cycle life Additional Product Info		• 270° rotation • One-way Torque • 3 torque values • Range 4.0 to 8.0 N-m • Black nylon housing • 20,000 cycle life Additional Product Info
PHC		PHCA	
	• 270° rotation • 8 torque values • Range 0.0 to 2.79 N-m • Zinc housing • Finish: plain or black • Standard or countersunk mounting holes • 50,000 cycle life Additional Product Info		• 270° rotation • 7 torque values • Range 0.44 to 2.79 N-m • Aluminum housing • Standard mounting holes • 50,000 cycle life Additional Product Info
PHCS		PH35	
	• 270° rotation • 7 torque values • Range 0.44 to 2.79 N-m • Stainless steel housing • Std or counter sunk mounting • 50,000 cycle life Additional Product Info		• High Torque • One-way Torque • 6 torque values • Range: 5.65 to 11.3 N-m • Zinc housing • 20,000 cycle life Additional Product Info
PHA 8mm		RT Series	
	• 360° rotation • 5 torque values • Range 0.28 to 0.65 N-m • Zinc housing • Std mounting holes • 50,000 cycle life Additional Product Info		• 4 part families: RT50, RT70, RT100, RT120 • 3 shaft end options: Flag, Straight, Exposed shaft • Dual-ended mounting option (RT-50, RT-70) • 14 torque values • Range: 0.11 to 5.65 N-m • Zinc or Black E-Coat Finish • 50,000 cycle life Additional Product Info




Standard Position Hinges & Torque Inserts

PHB		PHK	
	• 360° rotation • 7 torque values • Range 0.44 to 2.79 N-m • Zinc housing • Finish: plain or black • Std mounting holes • Left, right or dual ends • 50,000 cycle life		• 360° rotation • 5 torque values • Range 1.5 to 5.5 N-m • Zinc housing • 100% / 60% differential torque • 20,000 cycle life
	Additional Product Info		Additional Product Info
TI-C5M		TI-100 Series	
	• 360° rotation • 3 torque values • Range: 0.15 to 0.30 N-m • Designed for Press fit • Zinc Housing • 30,000 cycle life • Single fin design		• 360° rotation • 5 package sizes • 24 torque values • Range: 0.2 to 6.0 N-m • Designed for press fit • Black nylon housing • 25,000 cycle life • Single or dual fin design • One-way Torque (TI150/160)
	Additional Product Info		Additional Product Info
TI-200 Series		TI-300 Series	
	• 360° rotation • 2 packages sizes • 12 torque values • Range: 1.5 to 8.0 N-m • 100% / 60% differential torque • Designed for over molding • 20,000 cycle life (TI-240) • 10,000 cycle life (TI-220)		• 360° rotation • 4 package sizes, • 4 shaft-end attachment opts. • 12 torque values • Symmetric or One-way torque • Range: 0.5 to 10.0 Nm • Designed for press fit • 50,000 cycle life (TI-320,330) • 25,000 cycle life (TI-340,360)
	Additional Product Info		Additional Product Info
PHT		PHL	
	• 360° rotation • One-way Torque • 3 torque values • Range 2.0 to 6.0 N-m • Zinc housing • 20,000 cycle life		• 270° rotation • 6 torque values • Range 0.9 to 3.4 N-m • Zinc housing • Finish: plain or black • Standard mounting holes • 20,000 cycle life
	Additional Product Info		Additional Product Info
HTH60		SJ Series Spherical Joint	
	• Hollow axis design allows cable pass-through • Torques: 5.5 to 11.5 • 25,000 cycle life		• 3 size. With torques from 0.2 to 8.0 N-m • 60° up/down & left/right motion • Full 360° rotational adjustment • 50,000 adjustments life • Black nylon housing • SJ300 available with: • Optional AMPS mount adapter • Hidden Mounting option
	Additional Product Info		Additional Product Info




Standard Position Hinges & Torque Inserts


vTilt VESA Monitor Mount		vMX VESA Monitor Mount	
	- VESA std mounting pattern - Differential or One-way torque to provide easy lift - Torques from 3.0 to 8.0 N-m - Black nylon housing 20,000 cycle life		- VESA std mounting pattern - Adjusts in all directions: Tilt, Swivel, & Rotate - Torques from 5.0 to 7.0 N-m - Black or White nylon housing 50,000 adjustment life
	Additional Product Info		Additional Product Info
MH13		DX100– Multi-Axis Hinge	
	- Weight 24 grams 270° rotation 3 torque values - Range 1.0 to 3.0 N-m - Black nylon housing 25,000 cycle life		- Unique design allows full fold-over of panels is thin as 8mm. - Torque Range 0.3 to 1.5 N-m - Equal and mixed torque profiles 50,000 cycle life
	Additional Product Info		Additional Product Info
MH10		Visit reell.com for more information	
	- Weight 41.5 grams 270° rotation 3 torque values - Range 1.5 to 3.5 N-m - Black nylon housing 20,000 cycle life		
	Additional Product Info		



How A Reell Friction Hinge Works



The patented Reell friction hinge operates by providing torque along the axis of the hinge. In the hinge pictured at right, this is achieved by using a series of "clips" (1) that are pressed on to a shaft (2). The end of the shaft is attached to one side of the hinge (3), while the other side (4) is attached to the foot of the clips. When rotated, the clip/shaft interference provides a consistent static and dynamic torque.



Torque Range Chart

